


Light-Emitting Diode

Round LED

ELECSOUND®

Part Number	Chip			Lens Type	VF(V) If=20mA		IV(mcd) If=20mA	Angle 201/2
	Material	Emitted Color	Wave Length λD(nm)		Min	Max	Min Typ	
T-1 (3mm) Round LED (25deg)								
								
3004R4C-CPB-P	GaP	Red	640	Water Clear	1.8-2.3		50-100	25
3004R2C-CHC-S	GaAsP	Red	630-640	Water Clear	1.8-2.3		200-350	25
3004R1C-CSA-A	AlGaInP	Red	620-635	Water Clear	1.9-2.3		800-1200	25
3004R1C-CSB-B	AlGaInP	Red	620-635	Water Clear	1.9-2.3		1500-2000	25
3034R1C-CSC-C	AlGaInP	Red	620-635	Water Clear	1.9-2.3		3300-4000	25
3034R1C-CSE-D	AlGaInP	Red	620-635	Water Clear	1.9-2.3		10000-15000	25
3004Y1C-CSA-A	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3		800-1200	25
3004Y1C-CSB-B	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3		1500-2000	25
3034Y1C-CSC-C	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3		3300-4000	25
3034Y1C-CSE-D	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3		10000-15000	25
3004G6C-CHA-P	GaP	Green	565-575	Water Clear	1.9-2.3		50-100	25
3004G6C-CSA-S	AlGaInP	Green	565-575	Water Clear	1.9-2.3		1000-1500	25
3034G3C-CSC-A	InGaN	Green	520-530	Water Clear	2.9-3.3		3500-4800	25
3034G3C-CSE-B	InGaN	Green	520-530	Water Clear	2.9-3.3		12000-18000	25
3034B2C-CSB-A	InGaN	Blue	460-470	Water Clear	2.9-3.3		1500-2000	25
3034B2C-CSC-B	InGaN	Blue	460-470	Water Clear	2.9-3.3		3300-4000	25
3034B2C-CSD-C	InGaN	Blue	460-470	Water Clear	2.9-3.3		6000-8000	25
3034W2C-CSC-A	InGaN	White		Water Clear	2.9-3.3		2000-3500	25
3034W2C-CSD-B	InGaN	White		Water Clear	2.9-3.3		5000-6800	25
3034W2C-CUA-C	InGaN	White		Water Clear	2.9-3.3		10000-15000	25

Light-Emitting Diode

Round LED

ELECSOUND®

Part Number	Chip			Lens Type	VF(V) If=20mA		IV(mcd) If=20mA	Angle 201/2
	Material	Emitted Color	Wave Length λD(nm)		Min	Max	Min Typ	

T-1 (3mm) Round LED (40deg)



3004R1C-DHE-A	AlGaInP	Red	620-635	Water Clear	1.9-2.3	400-800	40
3004R1C-DSA-B	AlGaInP	Red	620-635	Water Clear	1.9-2.3	600-1000	40
3034R1C-DSB-C	AlGaInP	Red	620-635	Water Clear	1.9-2.3	1200-2000	40
3034R1C-DSD-D	AlGaInP	Red	620-635	Water Clear	1.9-2.3	3000-5000	40
3004Y1C-DHE-A	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	400-800	40
3004Y1C-DSA-B	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	600-1000	40
3034Y1C-DSB-C	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	1200-2000	40
3034Y1C-DSD-D	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	3000-5000	40
3004G6C-DSA-S	AlGaInP	Green	565-575	Water Clear	1.9-2.3	600-1000	40
3034G3C-DSB-A	InGaN	Green	520-530	Water Clear	2.9-3.3	2000-4000	40
3034G3C-DSD-B	InGaN	Green	520-530	Water Clear	2.9-3.3	4000-6000	40
3034B2C-DSA-A	InGaN	Blue	460-470	Water Clear	2.9-3.3	800-1200	40
3034B2C-DSB-B	InGaN	Blue	460-470	Water Clear	2.9-3.3	1000-2000	40
3034B2C-DSC-C	InGaN	Blue	460-470	Water Clear	2.9-3.3	2700-3500	40
3034W2C-DSA-A	InGaN	White		Water Clear	2.9-3.3	1500-2500	40
3034W2C-DSC-B	InGaN	White		Water Clear	2.9-3.3	2700-4000	40
3034W2C-DSE-C	InGaN	White		Water Clear	2.9-3.3	4500-6500	40
3004R4D-EPA-P	GaP	Red	640	Diffused	1.8-2.4	5-10	60
3004R2D-EPC-S	GaAsP	Red	630-640	Diffused	1.8-2.3	50-100	60
3004R1D-EHB-A	AlGaInP	Red	620-635	Diffused	1.9-2.3	100-150	60
3004R1D-EHC-B	AlGaInP	Red	620-635	Diffused	1.9-2.3	200-350	60
3034R1D-EHE-C	AlGaInP	Red	620-635	Diffused	1.9-2.3	1000-1500	60
3034R1D-ESA-D	AlGaInP	Red	620-635	Diffused	1.9-2.3	2000-3000	60
3004Y1D-EHB-A	AlGaInP	Yellow	580-595	Diffused	1.9-2.3	100-150	60
3004Y1D-EHC-B	AlGaInP	Yellow	580-595	Diffused	1.9-2.3	200-350	60
3034Y1D-EHE-C	AlGaInP	Yellow	580-595	Diffused	1.9-2.3	1000-1500	60
3034Y1D-ESA-D	AlGaInP	Yellow	580-595	Diffused	1.9-2.3	2000-3000	60
3004G6D-EPB-P	GaP	Green	565-575	Diffused	1.9-2.3	25-50	60
3004G6D-EHB-S	AlGaInP	Green	565-575	Diffused	1.9-2.3	100-250	60
3034G3D-EHE-A	InGaN	Green	520-530	Diffused	2.9-3.3	1500-2500	60
3034G3D-ESA-B	InGaN	Green	520-530	Diffused	2.9-3.3	2000-4000	60
3034B2D-EHD-A	InGaN	Blue	460-470	Diffused	2.9-3.3	400-600	60
3034B2D-EHE-B	InGaN	Blue	460-470	Diffused	2.9-3.3	800-1000	60
3034B2D-ESA-C	InGaN	Blue	460-470	Diffused	2.9-3.3	2000-3500	60
3034W2D-EHD-A	InGaN	White		Diffused	2.9-3.3	600-800	60
3034W2D-ESA-B	InGaN	White		Diffused	2.9-3.3	1000-2500	60
3034W2D-ESB-C	InGaN	White		Diffused	2.9-3.3	2500-4500	60
3002R1C-CSC-C	AlGaInP	Red	620-635	Water Clear	1.9-2.3	3300-4000	25
3002Y1C-CSC-C	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	3300-4000	25
3002B2C-CSD-C	InGaN	Blue	460-470	Water Clear	2.9-3.3	6000-8000	25
3002W2C-CSD-B	InGaN	White		Water Clear	2.9-3.3	5000-6800	25
3002B2C-CA	InGaN	Blue	460-470	Water Clear	2.9-3.3	3000-5000	25
3002W2C-CA	InGaN	White		Water Clear	2.9-3.3	5000-6000	25

Elecsound Technology Company Limited

TEL: 0086-755-82908842

FAX: 0086-755-83045964

Website: www.elecsound.com

Mail: sales@elecsound.com

Light-Emitting Diode

Round LED

ELECSOUND®

Part Number	Chip			Lens Type	VF(V) If=20mA		IV(mcd) If=20mA	Angle 201/2
	Material	Emitted Color	Wave Length λD(nm)		Min	Max	Min Typ	

T-1 3/4 (5mm) Round LED



5003R4C-BPC-P	GaP	Red	640	Water Clear	1.8-2.4	50-100	15
5003R2C-BHC-S	GaAsP	Red	630-640	Water Clear	1.9-2.3	250-400	15
5003R1C-BSA-A	AlGaInP	Red	620-635	Water Clear	1.9-2.3	1000-2000	15
5003R1C-BSB-B	AlGaInP	Red	620-635	Water Clear	1.9-2.3	2000-3500	15
5034R1C-BSC-C	AlGaInP	Red	620-635	Water Clear	1.9-2.5	4000-6000	15
5034R1C-BUA-D	AlGaInP	Red	620-635	Water Clear	1.9-2.5	10000-15000	15
5003Y1C-BSA-A	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	1000-2000	15
5003Y1C-BSB-B	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	2000-3500	15
5034Y1C-BSC-C	AlGaInP	Yellow	580-595	Water Clear	1.9-2.5	4000-5500	15
5034Y1C-BUA-D	AlGaInP	Yellow	580-595	Water Clear	1.9-2.5	10000-15000	15
5003G6C-BHA-P	GaP	Green	565-575	Water Clear	1.8-2.4	50-100	15
5003G6C-BSA-S	AlGaInP	Green	565-575	Water Clear	1.9-2.3	1000-2000	15
5034G3C-BSC-A	InGaN	Green	520-530	Water Clear	2.9-3.5	4000-6000	15
5034G3C-BUA-B	InGaN	Green	520-530	Water Clear	2.9-3.5	10000-15000	15
5034B2C-BSB-A	InGaN	Blue	460-470	Water Clear	2.9-3.5	1500-2500	15
5034B2C-BSC-B	InGaN	Blue	460-470	Water Clear	2.9-3.5	2000-4000	15
5034B2C-BSD-C	InGaN	Blue	460-470	Water Clear	2.9-3.5	6000-9000	15
5034W2C-BSC-A	InGaN	White		Water Clear	2.9-3.5	2000-4000	15
5034W2C-BSD-B	InGaN	White		Water Clear	2.9-3.5	6000-9000	15
5034W2C-BUB-C	InGaN	White		Water Clear	2.9-3.5	12000-18000	15


T-1 3/4 (5mm) Round LED (30Deg)

5003R1C-CSA-A	AlGaInP	Red	620-635	Water Clear	1.9-2.3	800-1500	30
5003R1C-CSB-B	AlGaInP	Red	620-635	Water Clear	1.9-2.3	1000-2500	30
5034R1C-CSC-C	AlGaInP	Red	620-635	Water Clear	1.9-2.5	3000-5000	30
5034R1C-CSE-D	AlGaInP	Red	620-635	Water Clear	1.9-2.5	8000-11000	30
5003Y1C-CSA-A	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	800-1500	30
5003Y1C-CSB-B	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	1000-2500	30
5034Y1C-CSC-C	AlGaInP	Yellow	580-595	Water Clear	1.9-2.5	3000-5000	30
5034Y1C-CSE-D	AlGaInP	Yellow	580-595	Water Clear	1.9-2.5	8000-11000	30
5003G6C-CSA-S	AlGaInP	Green	565-575	Water Clear	1.9-2.3	800-1200	30
5034G3C-CSC-A	InGaN	Green	520-530	Water Clear	2.9-3.5	3000-5000	30
5034G3C-CSE-B	InGaN	Green	520-530	Water Clear	2.9-3.5	8000-11000	30
5034B2C-CSB-A	InGaN	Blue	460-470	Water Clear	2.9-3.5	800-1500	30
5034B2C-CSC-B	InGaN	Blue	460-470	Water Clear	2.9-3.5	1000-2500	30
5034B2C-CSD-C	InGaN	Blue	460-470	Water Clear	2.9-3.5	5000-7000	30
5034W2C-CSB-A	InGaN	White		Water Clear	2.9-3.5	1500-3000	30
5034W2C-CSD-B	InGaN	White		Water Clear	2.9-3.5	4000-7000	30
5034W2C-CUA-C	InGaN	White		Water Clear	2.9-3.5	10000-15000	30

Light-Emitting Diode

Round LED

ELECSOUND®

Part Number	Chip			Lens Type	VF(V) If=20mA		IV(mcd) If=20mA	Angle 201/2
	Material	Emitted Color	Wave Length λD(nm)		Min	Max	Min Typ	
T-1 3/4 (5mm) Round LED (40-60Deg)								
								
5003R1C-DHE-A	AlGaInP	Red	620-635	Water Clear	1.9-2.3		400-800	40-60
5003R1C-DSA-B	AlGaInP	Red	620-635	Water Clear	1.9-2.3		600-1000	40-60
5034R1C-DSB-C	AlGaInP	Red	620-635	Water Clear	1.9-2.3		1200-2000	40-60
5034R1C-DSD-D	AlGaInP	Red	620-635	Water Clear	1.9-2.3		3000-5000	40-60
5003Y1C-DHE-A	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3		400-800	40-60
5003Y1C-DSA-B	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3		600-1000	40-60
5034Y1C-DSB-C	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3		1200-2000	40-60
5034Y1C-DSD-D	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3		3000-5000	40-60
5003G6C-DSA-S	AlGaInP	Green	565-575	Water Clear	1.9-2.3		600-1000	40-60
5034G3C-DSB-A	InGaN	Green	520-530	Water Clear	2.9-3.5		2000-4000	40-60
5034G3C-DSD-B	InGaN	Green	520-530	Water Clear	2.9-3.5		4000-6000	40-60
5034B2C-DSA-A	InGaN	Blue	460-470	Water Clear	2.9-3.5		800-1200	40-60
5034B2C-DSB-B	InGaN	Blue	460-470	Water Clear	2.9-3.5		1000-2000	40-60
5034B2C-DSC-C	InGaN	Blue	460-470	Water Clear	2.9-3.5		2700-3500	40-60
5034W2C-DSA-A	InGaN	White		Water Clear	2.9-3.5		1500-2500	40-60
5034W2C-DSC-B	InGaN	White		Water Clear	2.9-3.5		2700-4000	40-60

T-1 3/4 (5mm) Round Diffused LED								
5003R4D-EPB-P	Gap	Red	640	Diffused	1.8-2.4		5-10	50-60
5003R1D-EHB-A	AlGaInP	Red	620-635	Diffused	1.9-2.3		100-150	50-60
5003R1D-EHC-B	AlGaInP	Red	620-635	Diffused	1.9-2.3		200-350	50-60
5034R1D-ESA-C	AlGaInP	Red	620-635	Diffused	1.9-2.3		1000-1500	50-60
5034R1D-ESB-D	AlGaInP	Red	620-635	Diffused	1.9-2.5		2000-3000	50-60
5003Y1D-EHB-A	AlGaInP	Yellow	580-595	Diffused	1.9-2.3		100-150	50-60
5003Y1D-EHC-B	AlGaInP	Yellow	580-595	Diffused	1.9-2.3		200-350	50-60
5034Y1D-ESA-C	AlGaInP	Yellow	580-595	Diffused	1.9-2.3		1000-1500	50-60
5034Y1D-ESB-D	AlGaInP	Yellow	580-595	Diffused	1.9-2.5		2000-3000	50-60
5003G6D-EPB-P	GaP	Green	565-575	Diffused	1.8-2.4		25-50	50-60
5003G6D-EHB-S	AlGaInP	Green	565-575	Diffused	1.9-2.3		100-250	50-60
5034G3D-ESA-A	InGaN	Green	520-530	Diffused	2.9-3.5		1500-2500	50-60
5034G3D-ESB-B	InGaN	Green	520-530	Diffused	2.9-3.5		2000-4000	50-60
5034B2D-EHD-A	InGaN	Blue	460-470	Diffused	2.9-3.5		400-600	50-60
5034B2D-ESA-B	InGaN	Blue	460-470	Diffused	2.9-3.5		800-1000	50-60
5034B2D-ESB-C	InGaN	Blue	460-470	Diffused	2.9-3.5		2000-3500	50-60
5034W2D-EHE-A	InGaN	White		Diffused	2.9-3.5		600-800	50-60
5034W2D-ESA-B	InGaN	White		Diffused	2.9-3.5		1000-2500	50-60
5034W2D-ESB-C	InGaN	White		Diffused	2.9-3.5		2500-4500	50-60

Light-Emitting Diode

Round LED

ELECSOUND®

Part Number	Chip			Lens Type	VF(V) If=20mA		IV(mcd) If=20mA	Angle 201/2
	Material	Emitted Color	Wave Length λD(nm)		Min	Max	Min Typ	

8mm Round LED



8003R1C-CSA-A	AlGaInP	Red	620-635	Water Clear	1.9-2.3	800-1200	25
8003R1C-CSB-B	AlGaInP	Red	620-635	Water Clear	1.9-2.3	1500-2000	25
8034R1C-CSC-C	AlGaInP	Red	620-635	Water Clear	1.9-2.5	3000-4000	25
8034R1C-CSE-D	AlGaInP	Red	620-635	Water Clear	1.9-2.5	8000-9000	25
8003Y1C-CSB-A	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	800-1200	25
8003Y1C-CSB-B	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	1500-2000	25
8034Y1C-CSC-C	AlGaInP	Yellow	580-595	Water Clear	1.9-2.5	3000-4000	25
8034Y1C-CSE-D	AlGaInP	Yellow	580-595	Water Clear	1.9-2.5	8000-9000	25
8003G6C-CSA-S	AlGaInP	Green	565-575	Water Clear	1.9-2.3	800-1500	25
8034G3C-CSC-A	InGaN	Green	520-530	Water Clear	2.9-3.5	3000-4800	25
8034G3C-CSE-B	InGaN	Green	520-530	Water Clear	2.9-3.5	8000-9600	25
8034B2C-CSB-A	InGaN	Blue	460-470	Water Clear	2.9-3.5	1500-2000	25
8034B2C-CSC-B	InGaN	Blue	460-470	Water Clear	2.9-3.5	2000-4000	25
8034B2C-CSD-C	InGaN	Blue	460-470	Water Clear	2.9-3.5	6000-6800	25
8034W2C-CSC-A	InGaN	White		Water Clear	2.9-3.5	2000-3500	25
8034W2C-CSD-B	InGaN	White		Water Clear	2.9-3.5	6000-6800	25
8034W2C-CUA-C	InGaN	White		Water Clear	2.9-3.5	10000-12000	25
8003R1D-EHB-A	AlGaInP	Red	620-635	Water Clear	1.9-2.3	100-150	25
8003R1D-EHC-B	AlGaInP	Red	620-635	Water Clear	1.9-2.3	200-350	25
8034R1D-EHE-C	AlGaInP	Red	620-635	Water Clear	1.9-2.5	1000-1500	25
8034R1D-ESA-D	AlGaInP	Red	620-635	Water Clear	1.9-2.5	2000-3000	25
8003Y1D-EHB-A	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	100-150	25
8003Y1D-EHC-B	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3	200-350	25
8034Y1D-EHE-C	AlGaInP	Yellow	580-595	Water Clear	1.9-2.5	1000-1500	25
8034Y1D-ESA-D	AlGaInP	Yellow	580-595	Water Clear	1.9-2.5	2000-3000	25
8034G3D-EHE-A	InGaN	Green	520-530	Water Clear	2.9-3.5	1500-2500	25
8034G3D-ESA-B	InGaN	Green	520-530	Water Clear	2.9-3.5	2000-4000	25
8003G6D-EHB-S	AlGaInP	Green	565-575	Water Clear	1.9-2.3	100-250	25
8034B2D-EHD-A	InGaN	Blue	460-470	Water Clear	2.9-3.5	400-600	25
8034B2D-EHE-B	InGaN	Blue	460-470	Water Clear	2.9-3.5	800-1000	25
8034B2D-ESA-C	InGaN	Blue	460-470	Water Clear	2.9-3.5	2000-3500	25
8034W2D-EHD-A	InGaN	White		Water Clear	2.9-3.5	600-800	25
8034W2D-ESA-B	InGaN	White		Water Clear	2.9-3.5	1000-2500	25
8034W2D-ESB-C	InGaN	White		Water Clear	2.9-3.5	2500-4500	25

Elecsound Technology Company Limited

TEL: 0086-755-82908842

FAX: 0086-755-83045964


Website: www.elecsound.com

Mail: sales@elecsound.com

Light-Emitting Diode

Round LED

ELECSOUND®

Part Number	Chip			Lens Type	VF(V) If=20mA		IV(mcd) If=20mA	Angle 201/2
	Material	Emitted Color	Wave Length λD(nm)		Min	Max	Min Typ	
10mm Round LED								
								
10003R1C-CSA-A	AlGaInP	Red	620-635	Water Clear	1.9-2.3		800-1200	25
10003R1C-CSB-B	AlGaInP	Red	620-635	Water Clear	1.9-2.3		1500-2000	25
10034R1C-CSC-C	AlGaInP	Red	620-635	Water Clear	1.9-2.5		3000-4000	25
10034R1C-CSE-D	AlGaInP	Red	620-635	Water Clear	1.9-2.5		8000-9000	25
10003Y1C-CSA-A	AlGaInP	Yellow	580-595	Water Clear	1.9-2.3		800-1200	25
10003Y1C-CSB-B	AlGaInP	Yellow	580-595	Water Clear	1.9-2.5		1500-2000	25
10034Y1C-CSC-C	AlGaInP	Yellow	580-595	Water Clear	1.9-2.5		3000-4000	25
10034Y1C-CSE-D	AlGaInP	Yellow	580-595	Water Clear	1.9-2.5		8000-9000	25
10003G6C-CSA-S	AlGaInP	Green	565-575	Water Clear	2.9-3.5		800-1500	25
10034G3C-CSC-A	InGaN	Green	520-530	Water Clear	2.9-3.5		3000-4800	25
10034G3C-CSE-B	InGaN	Green	520-530	Water Clear	2.9-3.5		8000-9600	25
10034B2C-CSB-A	InGaN	Blue	460-470	Water Clear	2.9-3.5		1500-2000	25
10034B2C-CSC-B	InGaN	Blue	460-470	Water Clear	2.9-3.5		2000-4000	25
10034B2C-CSD-C	InGaN	Blue	460-470	Water Clear	2.9-3.5		6000-6800	25
10034W2C-CSB-A	InGaN	White		Water Clear	2.9-3.5		2000-3500	25
10034W2C-CSD-B	InGaN	White		Water Clear	2.9-3.5		6000-6800	25
10034W2C-CUA-C	InGaN	White		Water Clear	2.9-3.5		10000-12000	25
10003R1D-EHB-A	AlGaInP	Red	620-635	Diffused	1.9-2.3		200-450	40-60
10003R1D-EHC-B	AlGaInP	Red	620-635	Diffused	1.9-2.3		400-700	40-60
10034R1D-EHE-C	AlGaInP	Red	620-635	Diffused	1.9-2.5		800-1000	40-60
10034R1D-ESA-D	AlGaInP	Red	620-635	Diffused	1.9-2.5		1000-2500	40-60
10003Y1D-EHB-A	AlGaInP	Yellow	580-595	Diffused	1.9-2.3		200-450	40-60
10003Y1D-EHC-B	AlGaInP	Yellow	580-595	Diffused	1.9-2.5		400-700	40-60
10034Y1D-EHE-C	AlGaInP	Yellow	580-595	Diffused	1.9-2.5		800-1000	40-60
10034Y1D-ESA-D	AlGaInP	Yellow	580-595	Diffused	1.9-2.5		1000-2500	40-60
10003G6D-EHB-S	AlGaInP	Green	565-575	Diffused	2.9-3.5		200-450	40-60
10034G3D-EHE-A	InGaN	Green	520-530	Diffused	2.9-3.5		1000-2500	40-60
10034G3D-ESA-B	InGaN	Green	520-530	Diffused	2.9-3.5		2000-4500	40-60
10034B2D-EHD-A	InGaN	Blue	460-470	Diffused	2.9-3.5		600-800	40-60
10034B2D-EHE-B	InGaN	Blue	460-470	Diffused	2.9-3.5		800-1000	40-60
10034B2D-ESA-C	InGaN	Blue	460-470	Diffused	2.9-3.5		1000-2500	40-60
10034W2D-EHD-A	InGaN	White		Diffused	2.9-3.5		600-800	40-60
10034W2D-ESA-B	InGaN	White		Diffused	2.9-3.5		1000-2500	40-60
10034W2D-ESB-C	InGaN	White		Diffused	2.9-3.5		2000-4500	40-60

Elecsound Technology Company Limited

TEL: 0086-755-82908842

FAX: 0086-755-83045964

Website: www.elecsound.com

Mail: sales@elecsound.com